

SULFATREAT SELECT ULTRA



SULFATREAT SELECT ULTRA is a high-capacity, fast-reacting mixed-metal-oxide absorbent with enhanced macro-porosity for improved activity. This allows for smaller vessels and smaller product volumes in a given process application, providing flexibility in system design. SULFATREAT SELECT ULTRA is suitable for the removal of hydrogen sulfide, low-molecular-weight mercaptans and disulfides from gaseous hydrocarbons at low temperature. Desulfurization is achieved by reaction with mixed-metal oxides forming a stable metal sulfide.*

Typical Physical Properties

Nominal size	2.5 mm to 4.75 mm diameter
Form	Spherical granules
Composition.....	Proprietary
Packing density, lb/ft ³ (kg/L).....	59.3 to 74.9 (0.95 to 1.2)
Surface area	>40 m ² /g

Applications

- Reliable, predictable performance
- Operating flexibility
- Cost-effective sulfur removal
- Low pressure drop
- Impurity removal to very low levels
- Simple vessel changeouts
- Straightforward disposal of spent media

Packaging

SULFATREAT SELECT ULTRA can be supplied in both imperial and metric sizes; 1,000/2,000-lb or 0.5/1.0-m³ bulk bags.



Handling and Disposal

SULFATREAT SELECT ULTRA is a mixed-metal-oxide absorbent. Such materials can be handled safely provided that proper safety procedures, such as permit-to-work systems, and risk assessments, such as a Job Safety Analysis, chemical-handling assessments, lifting studies and applicable disposal regulations, are followed. It is recommended that an experienced contractor be engaged for product loading and discharge.

Desulfurization is achieved by reaction with mixed-metal oxides, forming a stable metal sulfide. The spent absorbent can be easily and safely recycled through the metals-recovery industry; the recycling routes are well established. SULFATREAT can facilitate the provision of product-disposal services if this is required.

About SULFATREAT

For over a decade, SULFATREAT has specialized in the removal of hydrogen sulfide from gas streams and liquids and today is an acknowledged industry leader. SULFATREAT processes are based on fixed-bed technology: simple, reliable and well-proven. Each SULFATREAT system is designed to address a specific set of process conditions, ensuring an optimized solution for the customer. Predictable performance results in media changeouts that can be planned in accordance with business requirements.



SULFATREAT
a business unit of M-I L.L.C.

U.S.A.
17998 Chesterfield Airport Road
Suite 215
Chesterfield, MO 63005
Toll-Free: 1-800-726-7687
Tel: +1-636-532-2211
Fax: +1-636-532-2764
www.sulfatreat.com
E-mail: info@sulfatreat.com

Asia Pacific
M.I. DRILLING FLUIDS
(MALAYSIA) SDN. BHD.
Kuala Lumpur, Malaysia
Tel: + 603-2161-7655
Fax: + 603-2161-7485
E-mail: info@sulfatreat.com

This information is supplied solely for informational purposes and M-I SWACO* makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data.
All product warranties and guarantees shall be governed by the Standard Terms of Sale.
Nothing in this document is legal advice or is a substitute for competent legal advice.